



Double Column Automatic Band Saw Machine

WH - 5046HA

Features :

1. Color touch screen.
2. Build-in eight languages for different area using.
3. Up to 10 jobs for cutting length and quantity setting.
4. A motor inverter controls variable blade speed.
5. Hydraulic blade tension device.
6. Fully stroke vise cylinders.
7. Rotary encoder measure precise feeding work piece length.
8. Uses hydraulic motor for auto chip conveyor driving.
9. Adds floating cylinders on shuttle vise jaws to easy feeding material.
10. Automatic malfunctions description, and remedy display.



威全機械工業股份有限公司

WAY TRAIN INDUSTRIES CO., LTD.

NO.1008, HOU CHUANG RD., PEI TUN CHU, TAICHUNG, TAIWAN, R.O.C.

TEL: 886-4-2422-3291 FAX: 886-4-2422-7689

E-mail :info@waytrain.com www.waytrain.com



TOUCH SCREEN CONTROL PANEL

Control panel design with touch screen system and indicator. Very easy to read and operate. Automatic error display, multiple settings and memory functions.



TUNGSTEN CARBIDE GUIDED

Using hydraulic to set tungsten carbide to guide the blade that is easy to operate and get stable function.



HYDRAULIC BLADE TENSION DEVICE

Blade tension device for easy blade tension setting, it is both quick and stable.

SPECIFICATIONS

WH-5046HA

Cutting Capacity (HxW)	○ 460 mm □ 460 x 500 mm
Blade Motor	7.5 HP
Hydraulic Motor	2HP
Coolant Motor	1/4 HP
Blade Size	41 x 1.3 x 5450mm
Blade Speed	30~85 MPM
Bundle Cutting (WxH)	195~310 mm x 120~230 mm
Table Height	850 mm
Feeding Stroke	500 mm
Minimum Residual Work Length	120 mm
Packing Size	2735 x 2260 x 2185 mm
N.W./G.W.	3090kg / 3485kg

WH - 5046HA

Optional Accessories



◎ 2-Meter roller stand



◎ Hydraulic vertical press device



◎ Pressure regulator for vises



◎ Chip cart

